



*The Art of Imitating Life*

EnvironMolds, LLC  
18 Bank Street  
Summit, NJ 07901

1-866-ARTMOLDS (278-6653)  
Fax: (908) 273-9256  
Internet: <http://www.artmolds.com>  
E-mail: [info@artmolds.com](mailto:info@artmolds.com)

---


**MATERIAL SAFETY DATA SHEET**

October 1, 2010

---

**HAZARD RATING**

---

	FLAMMABILITY			<u>HAZARD RATING</u>
				N 4 - EXTREME
TOXICITY			REACTIVITY	F 3 - HIGH
		SPECIAL		P 2 - MODERATE
				A 1 - SLIGHT
				0 - INSIGNIFICANT

---

**SECTION 1. PRODUCT IDENTIFICATION**

---

TRADE NAME: Del Milano™  
CHEMICAL NAME: Sulfur-Free Modeling Clay  
EMERGENCY PHONE: 1-866-278-6653  
1-908-273-5401  
EMERGENCY FAX: 1-908-273-9256

---

**SECTION 2. HAZARDOUS INGREDIENT INFORMATION**

---

This product is not hazardous as defined in 29 CFR 1900.1200. The composition of this clay is a trade secret as allowed by 29 CFR 1910.1200-48. In the event of a medical emergency, compositional information will be provided to a physician or nurse.

Product labeling conforms to ASTM D-4236 (no special label required).

---

SECTION 3.        PHYSICAL AND CHEMICAL DATA

---

Appearance and Odor:    Tan, slight odor.

Specific Gravity:        Varies between 1.05 – 1.65 g/cm<sup>3</sup>, depending on formula

Solubility in Water:    Negligible ( <1% )

Evaporation Rate:      N/A

Vapor Pressure:         N/A

Vapor Density:         N/A

Melting Point:         180 °F

---

SECTION 4.        HEALTH INFORMATION AND PROTECTION

---

NATURE OF HAZARD

EYE CONTACT:         Direct contact may irritate but will not injure eye tissue.

SKIN CONTACT:        Clay is regularly used with no skin protection.

INHALATION:          N/A

INGESTION:            May induce laxative effects.

FIRST AID

EYE CONTACT:         Flush with water.

SKIN CONTACT:        Modeling clay is normally used with no skin protection. If irritation appears, it is an allergic reaction and use should be discontinued.

INHALATION:          Normally not required.

INGESTION:            Normally not required.

---

SECTION 5.        FIRE AND EXPLOSION HAZARD

---

FLASHPOINT:            > 300 °F.

FLAMMABLE LIMITS:    N/A

SPECIAL FIRE FIGHTING INFORMATION:    Firefighters should use self-contained breathing apparatus to avoid exposure to smoke.

